

LSH-S-8-MO

MARINE OUTDOOR LIFT SYSTEM HEAVY WITH SWIVEL





UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET

TECHNICAL SHEET
ISSUE 001
SHEET 1

LSH-S-8-MO
MARINE OUTDOOR LIFT SYSTEM HEAVY WITH SWIVEL

future automation


MODEL	DESCRIPTION	MIN SCREEN HEIGHT	MAX SCREEN HEIGHT
LSH-S-5-MO	Vertical Lift with Swivel for 55" Screens	680 [26 3/4"]	800 [31 1/2"]
LSH-S-6-MO	Vertical Lift with Swivel for 65" Screens	800 [31 1/2"]	920 [36 1/4"]
LSH-S-7-MO	Vertical Lift with Swivel for 75" Screens	920 [36 1/4"]	1040 [40 15/16"]
LSH-S-8-MO	**Vertical Lift with Swivel for 85" Screens**	**1040 [40 15/16"]**	**1160 [45 11/16"]**
LSHZ-S-9-MO	Vertical Lift with Swivel for 98" Screens	1160 [45 11/16"]	1280 [50 3/8"]
LSHZ-S-10-MO	Vertical Lift with Swivel for 100" Screens	1280 [50 3/8"]	1400 [55 1/8"]
LSHZ-S-11-MO	Vertical Lift with Swivel for 115" Screens	1400 [55 1/8"]	1520 [59 13/16"]
LSHZ-S-12-MO	Vertical Lift with Swivel for 120" Screens	1520 [59 13/16"]	1640 [64 9/16"]

ADDITIONAL MOTOR OPTIONS:


SERVO DRIVEN TECHNOLOGY

Z - SERVO MOTOR
Higher lifting capacity & faster operation.
(Not applicable to swivel)
See LSHZ-S-MO Tech

ADDITIONAL FLAP OPTIONS:




DSP - DROP & SLIDE
See LSH-DSP-MO Tech




HF - HINGING FLAP
See LSH-HF-MO Tech


ADDITIONAL MOVEMENT OPTIONS:



STANDARD
See LSH-MO Tech



I - INVERTED
See I-LSH-MO Tech



EP - EXTENSION POLE
See LSH-S-EP-MO Tech

LSH-S-8-MO

MARINE OUTDOOR LIFT SYSTEM HEAVY WITH SWIVEL


future automation

SPECIFICATION	MEASUREMENTS
Maximum Screen Height	1160mm [45 11/16"]
Minimum Screen Height	1040mm [40 15/16"]
Maximum Lifting Capacity	100Kg [220lbs] (Higher Lifting Capacity Option Available, see LSHZ-S-8-MO)
Internal Cabinet Height	1470mm [57 7/8"]
Packaging Dimensions	TBC
Shipping Weight	TBC
Movement Type	Motorised
Speed	TBC
Power Supply Required	110V - 240V AC
Power Consumption	250 - 500W
Power Consumption Standby	3W
Mounting Patterns Supported	VESA 600, 400, 300 W x 600, 400, 300 H
Vertical Mounting Patterns Positioning	Mount holes in the bottom 115mm [4 1/2"] of the screen require a VOA Adaptor
Control Options	IR Remote, RS232, Contact Closure, RF Available
Colour Options	Custom RAL paint finishes
Package Contents	Mechanism, IR remote control
Marine Suitable	Yes
Outdoor Suitable	Yes


LSH-S-8-MO

MARINE OUTDOOR LIFT SYSTEM HEAVY WITH SWIVEL


GENERAL DIMENSIONS



Note:
For screens that are larger than 100mm [3 15/16"] the depths of the enclosure, base and top panel must be increased.



SECTION A-A
MECH DOWN



SECTION A-A
MECH UP


UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET


TECHNICAL SHEET
ISSUE 001
SHEET 4

LSH-S-8-MO

MARINE OUTDOOR LIFT SYSTEM HEAVY WITH SWIVEL


APERTURE DETAILS





DETAIL B

A suggested top panel and floor surface construction based upon the dimensions shown on sheet 6.




VIEWING SIDE

UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET


LSH-S-8-MO
MARINE OUTDOOR LIFT SYSTEM HEAVY WITH SWIVEL

BASE PANEL AND TOP PANEL DETAILS

BASE PANEL




Base thickness to be equal to or larger than the cabinet thickness.




SECTION C-C


[13/16"]



DETAIL E

TOP PANEL





SECTION D-D

NOTE: Changes to the top panel will affect the suggested dimension shown on sheet 5.

UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET

TECHNICAL SHEET
ISSUE 001
SHEET 6


LSH-S-8-MO
MARINE OUTDOOR LIFT SYSTEM HEAVY WITH SWIVEL

FIXED PANEL - INTEGRATION CONSIDERATIONS

General Mitigations:
- Activate hold-to-run/dead-man switch operation.
- Locate controls within direct line of sight of the mechanism.
- Implement password or key switch protected operation.

High Risk - Crushing Hazard
Crush hazard between the top panel and the cabinet top when the mechanism is closing.

Mitigation
The top panel is constructed to allow vertical movement in the presence of an obstruction, causing the mechanism to return to open again.



Low Risk - Falling Objects Hazard
Falling object hazard if objects are left on top of the top panel.

Mitigation
See general mitigations.

High Risk - Crushing Hazard
Crush hazard at the cabinet aperture when the mechanism is opening.

Mitigation
A Tapeswitch can be installed underneath the base panel to detect any obstructions. Scan the QR code and navigate to the Cabinet Guidelines document for further details.

Low Risk - Impact Hazard
Impact hazard around the mechanism when swivelling.

Mitigation
Set swivel limits to prevent impact with surrounding objects. See also general mitigations.

High Risk - Crushing Hazard
Crush hazard below the mechanism when the mechanism is closing.

Mitigation
Ensure the area below the mechanism is kept clear at all times when the mechanism is being used. If installing or maintaining the mechanism do so with the mechanism turned off.

Low Risk - Crushing Hazard
Cables could be snagged if not properly managed through and around the mechanism, causing damage to the mechanism and electronics.

Mitigation
Ensure sufficient cable slack is allowed around movement joints to prevent stretching and/or damage to the cables and/or the mechanism.

The installer is responsible for conducting a site-specific risk assessment. Due to the unique conditions of each installation, Future Automation cannot provide an exhaustive list of all potential risks.
Installers must ensure that all risks associated with installation, operation, and maintenance are identified and mitigated in accordance with applicable legislation and best practice.
Further safety and servicing guidance is available at:
www.futureautomation.net/safety

UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET


LSH-S-8-MO
MARINE OUTDOOR LIFT SYSTEM HEAVY WITH SWIVEL


BOX ENCLOSURE DETAILS

For size specific box enclosures with further details, please see CAD.

Maximum lifting capacity: 100kg [225lbs]

Z - SERVO MOTOR
Higher lifting capacity & faster operation.
(Not applicable to swivel)
See LSHZ-S-MO Tech





SECTION F-F

UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET

TECHNICAL SHEET
ISSUE 001
SHEET 8

LSH-S-8-MO
MARINE OUTDOOR LIFT SYSTEM HEAVY WITH SWIVEL


BOX ENCLOSURE - BOX ENCLOSURE BASE AND TOP SAFETY PANEL DETAILS

TOP PANEL


For top panel dimensions, please see sheet 6.

BOX ENCLOSURE BASE

Base thickness to be equal to or larger than the cabinet thickness.



TOP SAFETY PANEL



UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET

TECHNICAL SHEET
ISSUE 001
SHEET 9

LSH-S-8-MO
MARINE OUTDOOR LIFT SYSTEM HEAVY WITH SWIVEL

BOX ENCLOSURE - INTEGRATION CONSIDERATIONS

General Mitigations:
- Activate hold-to-run/dead-man switch operation.
- Locate controls within direct line of sight of the mechanism.
- Implement password or key switch protected operation.

High Risk - Crushing Hazard
Crush hazard between the base panel and the cabinet top as the lift closes.


Mitigation
The top panel is constructed to allow vertical movement in the presence of an obstruction, causing the mechanism to return to open again.

Low Risk - Crushing Hazard
Crush hazard at the cabinet aperture when mechanism is opening.

Mitigation
A Tapeswitch can be installed underneath the base panel to detect any obstructions. Scan the QR code and navigate to the Cabinet Safety document for further details.

High Risk - Crushing Hazard
Crush hazard below the mechanism when the mechanism is closing.

Mitigation
Ensure the area below the mechanism is kept clear at all times when the mechanism is being used. If installing or maintaining the mechanism do so with the mechanism turned off.



Low Risk - Falling Objects Hazard
Falling object hazard if objects are left on top of the top panel.

Mitigation
See general mitigations.

Low Risk - Impact Hazard
Impact hazard around the mechanism when swivelling.

Mitigation
Set swivel limits to prevent impact with surrounding objects. See also general mitigations.

Low Risk - Crushing Hazard
Cables could be snagged if not properly managed through and around the mechanism, causing damage to the mechanism and electronics.

Mitigation
Ensure sufficient cable slack is allowed around movement joints to prevent stretching and/or damage to the cables and/or the mechanism.

UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET

The installer is responsible for conducting a site-specific risk assessment. Due to the unique conditions of each installation, Future Automation cannot provide an exhaustive list of all potential risks.
Installers must ensure that all risks associated with installation, operation, and maintenance are identified and mitigated in accordance with applicable legislation and best practice.
Further safety and servicing guidance is available at:
www.futureautomation.net/safety


LSH-S-8-MO


MARINE OUTDOOR LIFT SYSTEM HEAVY WITH SWIVEL

SWIVEL DETAILS


The LSH-S can swivel a full 180° in both the clockwise and counterclockwise direction.


Top Panel hidden for clarity





Top Panel hidden for clarity





UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET

TECHNICAL SHEET
ISSUE 001
SHEET 11

LSH-S-8-MO
MARINE OUTDOOR LIFT SYSTEM HEAVY WITH SWIVEL

CABLE ROUTING


Screen cables should be routed through the cable management chain, under the beam and through the centre of the swivel pole up to the screen.

Mechanism cables should be routed to the control box, which should be stored in a safe and accessible location.

MECHANISM CABLES

MAINS POWER

SCREEN CABLES





UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET


TECHNICAL SHEET
ISSUE 001
SHEET 12


LSH-S-8-MO
MARINE OUTDOOR LIFT SYSTEM HEAVY WITH SWIVEL


CONTROL BOX DETAILS











NOTES

- ENCLOSURE AND CABLE GLANDS RATED TO IP56.
- ENCLOSURE AND LID FIXINGS ALL MADE FROM GEWISS GW PLAST 75.
- ENCLOSURE MATERIAL SUITABLE FOR TEMPERATURES +60˚C TO -25˚C.
- POWER SUPPLY UNIT (PSU) WILL ALLOW 110V OR 240V AC INPUT. THE SAME PSU IS USED FOR EU OR US MAINS SUPPLIES.
- OTHER THAN CONTROL CABLES, ALL CABLES TERMINATE AT CONTROL BOARD VIA STANDARD PHOENIX CONNECTORS.
- CABLE LOOM LENGTH SUPPLIED AT APPROX. 3m [118"]. LOOM CAN BE EXTENDED UP TO MAXIMUM OF APPROX. 10m [400"].
- MINIMUM CABLE BEND RADIUS 25mm [1"].

UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET

TECHNICAL SHEET
ISSUE 001
SHEET 13