

LSM-BE/PF 6
LIFT SYSTEM FOR BOX ENCLOSURE/PUSH FLAP

future automation





UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET

TECHNICAL SHEET
ISSUE 013
SHEET 1

LSM-BE/PF 6
LIFT SYSTEM FOR BOX ENCLOSURE/PUSH FLAP


future automation

SPECIFICATION	MEASUREMENTS
Maximum Screen Height	800mm (31 1/2")
Maximum Lifting Capacity	50Kg (110lb)
Maximum Lifting Capacity (Marine)	30Kg (66lb)
Internal Cabinet Height	950mm (37 3/8")
Decibel Rating	52 dB
Packaging Dimensions	1150 x 850 x 330mm (45 1/4" x 33 7/16 x 13")
Shipping Weight	35Kg (77lb)
Movement Type	Motorised
Power Supply Required	110V - 240V AC
Power Consumption	250 - 500W
Power Consumption Standby	3W
Mounting Patterns Supported	VESA 400, 300, 200 W x 400, 300, 200 H
Control Options	IR Remote, RS232, Contact Closure, RF Available
Product Options / Features	Specific B&O and Loewe mounts / adapters, Custom RAL paint finishes
Package Contents	Mechanism, IR remote control, Push Flap Kit, Box Enclosure Kit
Marine Suitable	Yes

LSM-BE/PF 6
LIFT SYSTEM FOR BOX ENCLOSURE/PUSH FLAP

future automation

[1 1/2"]
38
Maximum Possible Depth of Conduit




TOP VIEW

CABLE ROUTING


The LSM has an easily removable Mount Cover that cables from the screen can be routed underneath. Cables then travel through the centre of the Mount Boss and into the beam. Cables must be routed carefully to prevent any interference with the LSM beam as it operates.

Screen and Mechanism cables should be routed to a control box outside of the cabinet via an opening in the back of the cabinet or a conduit leading to the bottom.

SCREEN CABLES
MECHANISM CABLES
POWER CABLE



DETAIL A





UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET


TECHNICAL SHEET
ISSUE 013
SHEET 3


LSM-BE/PF 6
LIFT SYSTEM FOR BOX ENCLOSURE/PUSH FLAP

LSM-BE 6 - MECHANISM UP - IN CABINET










UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET


TECHNICAL SHEET
ISSUE 013
SHEET 4

LSM-BE/PF 6
LIFT SYSTEM FOR BOX ENCLOSURE/PUSH FLAP


LSM-BE 6 - MECHANISM DOWN - IN CABINET



Shown with tapered Box Enclosure Lid in square Cabinet Aperture.
A tapered Cabinet Aperture can be used to improve the fit.



DETAIL F



SECTION E-E

UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET

TECHNICAL SHEET
ISSUE 013
SHEET 5


LSM-BE/PF 6


LIFT SYSTEM FOR BOX ENCLOSURE/PUSH FLAP

BOX ENCLOSURE BASE PANEL AND LID DETAILS


NOTE: A tapered Box Enclosure Lid creates a good fit in the Cabinet Aperture and helps the Box Enclosure to locate within the cabinet.


BOX ENCLOSURE LID (TAPERED) TOP VIEW







BASE PANEL TOP VIEW





BASE PANEL BOTTOM VIEW





SECTION G-G


UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET


TECHNICAL SHEET
ISSUE 013
SHEET 6


LSM-BE/PF 6
LIFT SYSTEM FOR BOX ENCLOSURE/PUSH FLAP

LSM-PF 6 - MECHANISM UP - IN CABINET


SECTION I-I







SECTION H-H




DETAIL J


UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET

TECHNICAL SHEET
ISSUE 013
SHEET 7


LSM-BE/PF 6
LIFT SYSTEM FOR BOX ENCLOSURE/PUSH FLAP


LSM-PF 6 - MECHANISM DOWN - IN CABINET





DETAIL L





SECTION K-K

UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET

LSM-BE/PF 6
LIFT SYSTEM FOR BOX ENCLOSURE/PUSH FLAP


PUSH FLAP BASE PANEL AND FLAP DETAILS

Flap depth dimensions are based on a 3mm thick piano hinge
Required flap dimensions may vary dependant on the hinge used


FLAP PANEL - BOTTOM VIEW



A step is required on the front of the flap to meet a step in the front edge of the cabinet aperture





DETAIL N




SECTION M-M


BASE PANEL - TOP VIEW





BASE PANEL - BOTTOM VIEW






SECTION O-O


UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET

TECHNICAL SHEET
ISSUE 013
SHEET 9

LSM-BE/PF 6
LIFT SYSTEM FOR BOX ENCLOSURE/PUSH FLAP


BOX ENCLOSURE POSITION ADJUSTMENT






SECTION P-P

The countersink bolts enable fine tuning the position of the box enclosure relative to the uprights





DETAIL Q

UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET


TECHNICAL SHEET
ISSUE 013
SHEET 10

LSM-BE/PF 6
LIFT SYSTEM FOR BOX ENCLOSURE/PUSH FLAP


SCREEN MOUNT ADJUSTABILITY

A standard adjustable height VESA 400 mount is included. This is also compatible with VESA 300 and 200 mounting patterns


Separate VESA 300 and 200 mounts are available.




V400




V300



V200







UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET

LSM-BE/PF 6
LIFT SYSTEM FOR BOX ENCLOSURE/PUSH FLAP

MECHANISM INSTALLTION OVERVIEW






UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET


LSM-BE/PF 6
LIFT SYSTEM FOR BOX ENCLOSURE/PUSH FLAP


OVERALL MECHANISM DIMENSIONS

MECHANISM - UP POSITION



MECHANISM - DOWN POSITION





UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET

TECHNICAL SHEET
ISSUE 013
SHEET 13