

MDM-SPLIT T1160
MOVING DOOR MECHANISM

future automation

Open Position



Closed Position




UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET

TECHNICAL SHEET
ISSUE 001
SHEET 1


MDM-SPLIT T1160
MOVING DOOR MECHANISM

future automation

PANELS CLOSED



PANELS OPEN





UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET


TECHNICAL SHEET
ISSUE 001
SHEET 2

MDM-SPLIT T1160
MOVING DOOR MECHANISM

GENERAL DIMENSIONS








SECTION A-A
SCALE 1 : 3

UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET

TECHNICAL SHEET
ISSUE 001
SHEET 3


MDM-SPLIT T1160
MOVING DOOR MECHANISM

SWITCH ADJUSTMENT




DETAIL D
SCALE 1 : 2


The limit switches can be adjusted using an allen key. Undo the bolts and slide switch to desired position.



UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET

MDM-SPLIT T1160
MOVING DOOR MECHANISM





NOTES

- POWER SUPPLY UNIT (PSU) WILL ALLOW 110V OR 240V AC INPUT. THE SAME PSU IS USED FOR EU OR US MAINS SUPPLIES.
- OTHER THAN CONTROL CABLES, ALL CABLES TERMINATE AT CONTROL BOARD VIA STANDARD PHOENIX CONNECTORS.
- CABLE LOOM LENGTH SUPPLIED AT APPROX. 3m [118"]. LOOM CAN BE EXTENDED UP TO MAXIMUM OF APPROX. 10m [400"].
- MINIMUM CABLE BEND RADIUS 25mm [1"].

UK +44 (0) 1438 833577 **US** +1 (603) 742 9181
www.**FUTUREAUTOMATION**.NET

TECHNICAL SHEET
ISSUE 001
SHEET 5